European Copper Termination Adapter Kit Instructions ECA-8 and ECA-12

Construct chase as illustrated in Figure 1. The shortest vertical side must be at least 30" high and the minimum inside dimension must be at least 19". Top of chimney system should align with chase top. Slip adapter sleeve into inner pipe of chimney system as shown in Figure 2. Place gas separator around adapter sleeve and secure in position by inserting tabs inside slots as shown in Figure 3 (model ECA-8 shown).




Figure 1 - Constructing Chase

Parts included with this kit: ECA-8

8" European Copper Termination Adapter Kit

Gas Separator PN 124317-01Adapter Sleeve PN 20705

ECA-12

12" European Copper Termination Adapter Kit

Gas Separator PN 20819Adapter Sleeve PN 110004-01




Figure 2 - Installing Adapter Sleeve




Figure 3 - Installing Gas Separator

Termination adapter kit models ECA-8 and ECA-12 <u>must</u> be used with the approved copper chimney pot models listed below.

The following European copper chimney pot models are approved for use with DESA 8" and 12" model woodburning fireplaces:

• ECP1L	Copper Chimney Pot – King	EC-O-2447-1
• ECP2L	Copper Chimney Pot – Queen	EC-O-2039-1
• ECP3L	Copper Chimney Pot – Pawn	EC-O-1924-1
• ECP4L	Copper Chimney Pot – Knight II	EC-SQ-1633-1
• ECP5L	Copper Chimney Pot – Knight	EC-SQ-2144-1
• ECP6L	Copper Chimney Pot – Bishop	EC-R-2649-1
• ECP7L	Copper Chimney Pot – Bishop II	EC-R-2036-1





124318 01 NOT A UPC